

Double-Sided Polyester Tape

A high clarity, clear double-sided polyester tape, .22mm thick coated with a solvent acrylic adhesive and a red OPP die cuttable release liner. The tape features excellent adhesion and holding force to a wide variety of surfaces.

FEATURES

The product is a high performance double-sided polyester tape with excellent initial tack and high sheer adhesion. It displays excellent UV, weather and temperature tolerance. The product also exhibits a high resistance to plasticiser and features moisture stability and chemical resistance.



APPLICATION

Ideally suited to a wide variety of industries which include:

- Curtains & Blinds
- Trim Mounting
- Acrylic Bonding
- Signage & Display
- Extruded Plastic Profiles

SPECIFICATIONS			
Total Thickness	0.215mm – 0.225mm	Holding Power for Temp (60C)	> 24 hrs 0.5kg/2.5cm x 0.5cm
Coating Thickness	0.095mm – 0.100mm	Adhesion	> 2.5kg/2.5cm
Initial Tack (A/B Side)	< 5cm	Solvent Resistance	Good
Holding Power	> 24 hrs 1kg/2.5cm x 2.5cm	Available Widths	6.0mm - 1250mm

Terms & Conditions

This product should be applied to a clean and dry surface. The above figures represent average values. The selection of a tape is the responsibility of the buyer. Tape should be stored at room temperature and should not be exposed to sunlight. We reserve the right to make changes without notice to our product and specifications.